

Market introduction

January 2024

GEOMETRY

FLORENT COIRIER (FR)



STIG MYLER (DK)



FLORENT COIRIER (FR)



FLORENT COIRIER (FR)



STIG MYLER (DK)



STIG MYLER (DK)




DESIGN | INTERNATIONAL COLLECTIVE



GEOMETRY | ○



GEOMETRY | □□



DESIGN | INTERNATIONAL COLLECTIVE



ENGINEER | LUKAS WEYHAEGHE






GEOMETRY | PRODUCT GROUPS



GEOMETRY SUSPENDED ADJ 672



GEOMETRY SUSPENDED ADJ 672X672




GEOMETRY SUSPENDED ADJ 672X1288


GEOMETRY | 360°



GEOMETRY | STREAMLINED



GEOMETRY | COLORS





GEOMETRY | COLOURS





GEOMETRY | COLOURS

















GEOMETRY | INFINITY AND BEYOND




GEOMETRY | INFINITY AND BEYOND





GEOMETRY | POWERFEED




POWER FEED SURFACE





POWER FEED RECESSED



GEOMETRY | SUSPENSION KITS



SUSP. KIT 672



672X672 / 672X1288



GEOMETRY | TECHNOLOGY

Geometry
3000K
CRI90+
2317 lm
110lm/W
DE (24V LED driver 60W, 100 or 150W) (Non dim/1-10V or pushdim/dali)
L80B10 @ 50.000 hrs

Geometry, 3000K, white structure



Track 48V

MECHANICAL CONNECTIONS CURVED

TRACK 48V | MECHANICAL CONNECTION CURVED



TRACK 48V | MECHANICAL CONNECTION CURVED



90°

135°

TRACK 48V | MECHANICAL CONNECTION CURVED





PISTA TRACK 48V | MECHANICAL CONNECTION CURVED



90°



135°



135°




135°

135°

135°

135°





90°

90°

Chival

Surface-mounted wall lighting DI



DUELL

SPLIT

TRAPZ

SULFER

BOLD

SMART TUBE WALL

2004

2012


2014

2016


2017

2017











"CHIVAL"

↳ shield
chivalry


up & down
wall light.




side.



top.




1 sheet
folded!



front.


\$ 200.


CHIVAL



2020.



ENGINEER | LIAM DE BRABANDERE













































Chival| specifications

Chival	Chival WD
2700K 3000K	1800-3000K
CRI90	CRI95
713 lm ⁽¹⁾	482 lm ⁽²⁾
11,6 W ⁽¹⁾	10,6 W ⁽²⁾
61 lm/W ⁽¹⁾	45 lm/W ⁽²⁾
IP20	IP20
DE Trailing Edge Dali/Push-Dim	


(1) 3000K, Grey White Structure
(2) Grey White Structure

CASAMBI



Minude



















Modest

C




c





Modest
2700K
CRI90+
25°
IP55
739 lm
7,2W
103 lm/W
dimnable



CASAMBI



Always check our website for the most complete and up to date specifications!

IMPULSE

MAARTEN DE CEULAER (BE)






JOSEF ALBERS

INTERACTION OF COLOR

*"Every perception of colour is an illusion...
We do not see colors as they really are.
In our perception they alter one another"*



MARCH 25 - MAY 29 1999 GUGGENHEIM MUSEUM, NEW YORK

MAARTEN DE CEULAER (BE)




ENGINEER | VINCENT CHANTERIE




IMPULSE | A POEM OF LIGHT AND SHADOW






IMPULSE | ROUND WALL




IMPULSE | SQUARE WALL











IMPULSE | TECHNOLOGY

Impulse
2700K 3000K
CRI90+
630 lm
84lm/W
7.5W
DI (IP20) Tre dim, dali/pushdim or 1-10V DE (IP44)
L80B10 @ 50.000 hrs

Impulse round wall, 3000K, white structure

